

WiCAM



DIGITAL WIRELESS IP CAMERA SOLUTION WITH SOLAR POWER



DYNAMIC RAPIDLY DEPLOYED VIDEO SURVEILLANCE SOLUTION

Spytek Security Solutions

DIGITAL IP VIDEO SURVEILLANCE EXPERTS



APPLICATIONS

CONSTRUCTION MONITORING

Watch construction activity as it happens. Zoom in on details and snap pictures from the live video.

MARKETING – LIVE WEBCAMS

Provide live feeds of live events and views of your hotels, clubs, restaurants

REAL ESTATE MONITORING

Ad-Hoc property surveillance to prevent vandalism and theft.

COMMERCIAL SECURITY

Quick and hassle free deployment for instant or long-term surveillance and monitoring.

SIMPLY WiCAM – No Internet, No Power, NO PROBLEM!!

WiCAM systems are shipped fully configured and tested to support any of the major broadband wireless carriers. With a variety of mounting options, the WiCAM is the most versatile system of its kind. Plug-n-play agility sets the WiCAM apart from similar systems. Using either Power-over-Ethernet or optional solar power.

Includes remote-controllable network camera inside all-weather enclosure with heating/cooling; pole and wall mounting brackets; and 120V AC power supply (Pole not included)

OPTIONAL ACCESSORIES:
Solar Power Plant to power the camera.

CALL RIGHT NOW TO GET MORE INFORMATION
760-740-9660

- ✓ Completely self contained systems for capture and transmit of video over wireless networks.
- ✓ View video real-time via WiFi connection, and/or cellular broadband.
- ✓ View and remote control camera over broadband or wireless connection

- **HIGH RESOLUTION CAMERA:**

- Day/Night capability
- On board SD Video Storage

- **WAN + WiFi router:**

- Connect to the Internet through any 3g/4g carrier or ISP via WiFi Link
- Transmit video to a SAN, NAS or other network connected storage.
- Connect through closed wireless network via 802.11(n)
- Power Over Ethernet

- **ALSO INCLUDED:**

- Blower Fan,
- Power-Over-Ethernet w/ two line support to 25W

- **OPTIONAL INTERFACE EXTENSION UNIT:**

- Power up to 8 Cameras with PoE switch
- Load Balancing unit for added bandwidth over the cellular network
- Fail-over capability

OPERATIONAL IN MINUTES
NO COMPLICATED SET UP NEEDED

CAMERA FEATURES

- No additional housings, fans, heaters or mounts needed
- No additional software required...all software included
- No moving parts to fail
- Built in Linux based PC
- Up to 64GB SD flash memory on board camera
- Record directly to NAS, RAID 0, 1, 5, 6, 10
- Image processing at camera level - low network load
- Power Over Ethernet (POE)
- Telephone, email & text messaging upon alarm/event
- Superior Optics, Engineering & Reliability
- Brilliant Image Quality

CELL MODEM FEATURES

- Embedded Intelligence
- High-Speed Processor Machine Protocols

BENEFITS:

- Persistent Network Connectivity
- High-Speed 2-Way Data
- Certified for Hazardous Environments
- Remote Management and Configuration

PHYSICAL SPECIFICATIONS

Enclosure Size(H x W x L): 7" x 5" x 21.5"
 Enclosure Type: Extruded Aluminum Outdoor
 Side opening lid: Lockable
 Mounting: Wall mount, Pole mount adapter included (1.5" to 8" diameter)
 Options: Sun shroud, Support strut
 Operating Temperature: 20°F to 120°F
 Certifications NEMA 3R
 Weight 12 pounds
 Power: 120V AC

Field Engineering & Installation Support
Available Upon Request

CALL/EMAIL TO GET MORE INFORMATION
760-740-9660 / INFO@SPYTEKSECURITY.COM